

Model

KE010/KE016/  
KE028/KE040/KE050

## ● 性能

型号	扭矩 (Nm)			开关时间 50Hz/60Hz(sec)	额定电流 (A)					负载率 (%)	电机 绝缘等级	手轮转数
	0°	45°	90°		AC(1PHASE)		AC(1PHASE)		DC			
					110V	220V	380V	440V	24V			
KE010-3P	100	65	100	22/18	0.5	0.3	N/A	N/A	3	S2 40%	*F	15
KE010-4P	80	50	80	18/14	0.5	0.3	N/A	N/A	3	S2 40%	*F	11
KE010-5P	60	40	60	14/11	0.5	0.3	N/A	N/A	3	S2 40%	*F	9
KE016-3P	160	107	160	28/23	1.05	0.55	N/A	N/A	5	S2 40%	*F	19
KE016-4P	130	85	130	22/18	1.05	0.55	N/A	N/A	5	S2 40%	*F	16
KE016-5P	100	65	100	18/14	1.05	0.55	N/A	N/A	5	S2 40%	*F	13
KE028-3P	280	190	280	40/33	1.05	0.55	N/A	N/A	5	S2 40%	*F	23
KE028-4P	240	160	240	30/25	1.05	0.55	N/A	N/A	5	S2 40%	*F	19
KE028-5P	190	125	190	24/20	1.05	0.55	N/A	N/A	5	S2 40%	*F	15
KE040-3P	400	270	400	40/33	1.5	0.7	0.15	0.16	7	S2 40%	*F	23
KE040-4P	350	240	350	30/25	1.5	0.7	0.15	0.16	7	S2 40%	*F	19
KE040-5P	300	220	300	24/20	1.5	0.7	0.15	0.16	7	S2 40%	*F	15
KE050-3P	500	350	500	40/33	2	1	0.28	0.30	N/A	S2 40%	F	23
KE050-4P	450	310	450	30/25	2	1	0.28	0.30	N/A	S2 40%	F	19
KE050-5P	400	280	400	24/20	2	1	0.28	0.30	N/A	S2 40%	F	15

## ● 标准参数

外壳	防护等级 IP67
电机电源	110V, 220V AC 50Hz/60Hz, 24V DC
负载率	S2 40%, 最大30秒
指示器	圆顶型机械指示器
限位开关	2X 开/关 (SPDT 250VAC/16A)
手动操作	KE010~KE016 ; 6mm六角扳手(HEX.) KE028~KE050 ; 8mm六角扳手(HEX.)
行程	90°±5°
接线孔	2-PF1/2"
环境温度	-20℃~+60℃
外涂层	粉末喷涂
干燥器	1PH 220V/110 5W