

AS单作用系列扭矩表

unit : Nm

Model	Angle	Spring torque: Weak		Spring torque: Middle		Spring torque: Strong	
		Spring to Close	Air to Open:3Bar	Spring to Close	Air to Open:4.5Bar	Spring to Close	Air to Open:6Bar
AS50	0°	10.0	20.0	14.0	26.0	17.0	34.0
	45°	9.0	9.0	12.0	12.0	15.0	15.0
	90°	20.0	10.0	26.0	14.0	34.0	17.0
AS65	0°	22.0	39.0	35.0	54.0	48.0	70.0
	45°	18.0	18.0	23.0	28.0	37.0	32.0
	90°	39.0	22.0	54.0	35.0	70.0	48.0
AS80	0°	40.0	70.0	60.0	100.0	80.0	130.0
	45°	30.0	30.0	50.0	50.0	70.0	70.0
	90°	70.0	40.0	100.0	60.0	130.0	80.0
AS100	0°	70.0	140.0	100.0	190.0	130.0	240.0
	45°	50.0	50.0	80.0	80.0	110.0	110.0
	90°	140.0	70.0	190.0	100.0	240.0	130.0
AS125	0°	175.0	251.0	243.0	403.0	358.0	520.0
	45°	105.0	125.0	177.0	182.0	215.0	254.0
	90°	215.0	168.0	395.0	210.0	441.0	341.0
AS140	0°	200.0	370.0	371.0	576.0	480.0	726.0
	45°	170.0	170.0	236.0	265.0	330.0	360.0
	90°	370.0	200.0	447.0	366.0	680.0	430.0
AS160	0°	400.0	540.0	550.0	750.0	769.9	1,149.9
	45°	290.0	290.0	420.0	420.0	560.0	560.0
	90°	540.0	400.0	750.0	550.0	1,149.9	769.9
AS185	0°	641.7	866.3	882.3	1,203.1	1,235.2	1,844.8
	45°	445.8	445.8	645.7	645.7	860.9	860.9
	90°	794.1	588.2	1,102.9	808.8	1,691.1	1,132.3
AS210	0°	840.0	910.0	1,250.0	1,510.0	1,750.0	2,160.0
	45°	500.0	430.0	740.0	780.0	1,040.0	1,130.0
	90°	1,000.0	500.0	1,500.0	920.0	2,140.0	1,370.0
AS250	0°	1,540.0	1,900.0	2,120.0	2,760.0	3,060.0	3,660.0
	45°	920.0	950.0	1,320.0	1,370.0	1,830.0	1,900.0
	90°	1,800.0	1,400.0	2,470.0	2,200.0	3,550.0	2,760.0
AS300	0°	2,870.0	4,283.0	4,308.0	6,421.0	5,740.0	8,566.0
	45°	1,447.0	1,523.0	2,172.0	2,283.0	2,894.0	3,046.0
	90°	2,928.0	2,180.0	4,396.0	3,266.0	5,857.0	4,359.0

▪ 弹簧分为 强/中/弱 三种供您选择, 如订单上没有特别标注, 以标准 (蓝色框) 出货。

* 科仁加公司保留以上数据得最终解释权, 如有变更, 恕不另行通知, 请咨询0531-88588198。

2015年5月23日