

RS单作用系列扭矩表																	unit : Nm
Model	Spring unit	Supply Air															
		3Bar		4Bar		4.5Bar		5Bar		6Bar		7Bar		SPRING			
		0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	90°	0°		
RS40	1	2.8	1.8	4.9	3.8	5.8	4.7	6.7	5.6	8.6	7.5	10.4	9.3	2.8	1.8		
	2	-	-	-	-	3.6	1.4	4.5	2.3	6.4	4.2	8.2	6.0	6.4	4.2		
	op3	2.5	1.1	4.3	3.0	5.3	3.9	6.2	4.8	8.0	6.6	9.8	8.5	3.9	2.5		
	op4	-	-	3.8	2.1	4.6	3.0	5.6	4.0	7.5	5.8	9.3	7.6	4.6	3.0		
	op5	-	-	-	-	4.2	2.2	5.1	3.2	6.9	5.0	8.7	5.0	5.5	3.6		
RS50	8	4.7	2.3	8.1	5.7	9.9	7.4	11.5	9.1	15.0	12.6	18.4	16.0	8.0	5.6		
	9	-	-	7.4	4.6	9.2	6.4	10.8	8.0	14.3	11.5	17.7	14.9	9.1	6.3		
	10	-	-	6.8	3.7	8.5	5.5	10.2	7.1	13.7	10.6	17.1	14.0	10.0	6.9		
	11	-	-	-	-	7.8	4.4	9.5	6.1	13.0	9.6	16.4	13.0	11.0	7.6		
	12	-	-	-	-	-	-	-	-	12.3	8.5	15.7	11.9	12.1	8.3		
RS65	8	9.6	4.7	16.0	11.1	19.2	14.3	22.4	17.5	28.7	23.8	35.1	30.2	14.4	9.5		
	9	-	-	14.8	9.3	18.0	12.5	21.2	15.6	27.6	22.0	34.0	28.4	16.2	10.6		
	10	-	-	13.6	7.5	16.8	10.6	20.0	13.8	26.4	20.2	32.8	26.6	18.0	11.8		
	11	-	-	-	-	15.6	8.8	18.8	12.0	25.2	18.4	31.6	24.8	19.8	13.0		
	12	-	-	-	-	-	-	-	-	24.1	16.7	30.4	23.1	21.5	14.2		
RS80	8	19.1	7.7	32.1	20.7	38.7	27.3	45.2	33.8	58.3	46.9	71.3	60.0	30.7	20.1		
	9	-	-	29.6	16.7	36.2	23.3	42.7	29.8	55.7	42.9	68.8	56.0	35.5	22.6		
	10	-	-	27.1	12.9	33.7	19.5	40.4	25.9	53.2	39.0	66.3	52.1	39.4	25.1		
	11	-	-	-	-	31.2	15.5	37.7	22.0	50.7	35.0	63.8	48.1	43.3	27.6		
	12	-	-	-	-	-	-	-	-	48.2	31.2	61.3	44.3	47.2	30.1		
RS90	8	27.2	9.5	46.4	28.8	56.2	38.5	65.8	48.1	85.0	67.4	104.3	86.6	48.3	30.6		
	9	-	-	42.6	22.7	52.3	32.4	61.9	42.0	81.2	61.3	100.4	80.5	54.4	34.5		
	10	-	-	38.7	16.6	48.4	26.4	58.0	36.0	77.3	55.2	96.5	74.5	60.5	38.4		
	11	-	-	-	-	44.7	20.4	54.3	30.0	73.5	49.3	92.8	68.5	66.4	42.1		
	12	-	-	-	-	-	-	-	-	69.7	43.2	88.9	62.4	72.5	46.0		
RS100	8	42.6	19.5	70.8	47.6	84.8	61.6	98.9	75.7	127.0	103.8	155.1	131.9	64.9	41.7		
	9	-	-	65.5	39.4	79.5	53.5	93.6	67.6	121.7	95.7	149.9	123.8	73.0	47.0		
	10	-	-	60.3	31.3	74.3	45.3	88.4	59.4	116.5	87.6	144.6	115.7	81.2	52.2		
	11	-	-	-	-	69.1	37.2	83.2	51.3	111.3	79.4	139.5	107.5	89.3	57.4		
	12	-	-	-	-	-	-	-	-	106.1	71.4	134.2	99.5	97.3	62.6		
RS115	8	56.4	25.7	93.6	62.9	112.1	81.5	130.8	100.1	168.0	137.3	205.1	174.5	85.8	55.2		
	9	-	-	86.6	52.2	105.2	70.7	123.8	89.4	161.0	126.5	198.2	163.7	96.6	62.1		
	10	-	-	79.7	41.4	98.2	59.9	116.9	78.6	154.1	115.8	191.2	153.0	107.3	69.1		
	11	-	-	-	-	91.4	49.2	110.1	67.8	147.3	105.0	184.4	142.2	118.1	75.9		
	12	-	-	-	-	-	-	-	-	140.3	94.4	177.5	131.6	128.7	82.8		
RS125	8	84.7	35.2	141.8	92.4	170.4	120.9	198.9	149.5	256.0	206.5	313.0	263.6	136.0	86.5		
	9	-	-	131.0	75.9	159.5	104.4	188.1	133.0	245.1	190.0	302.2	247.1	152.4	97.3		
	10	-	-	120.2	58.4	148.7	86.9	177.3	115.5	234.3	172.5	291.4	229.6	170.0	108.2		
	11	-	-	-	-	137.4	70.5	165.9	99.0	223.0	156.0	280.1	213.1	186.4	119.5		
	12	-	-	-	-	-	-	-	-	212.7	138.5	269.8	195.6	203.9	129.8		
RS140	8	79.7	10.7	201.4	132.4	241.9	172.9	282.5	213.5	363.6	294.6	444.7	375.7	192.0	123.1		
	9	-	-	186.4	108.1	227.0	148.7	267.5	189.2	348.6	270.3	429.7	351.4	216.3	138.0		
	10	-	-	170.6	83.9	211.1	124.4	251.7	165.0	332.8	246.1	413.9	327.2	240.5	153.8		
	11	-	-	-	-	196.2	101.1	236.8	141.7	317.9	222.8	399.0	303.9	263.8	168.7		
	12	-	-	-	-	-	-	-	-	302.0	198.6	383.1	279.7	288.0	184.6		
RS160	8	165.3	76.7	282.2	193.6	340.6	252.0	399.0	310.4	515.9	427.3	632.8	544.3	274.0	185.4		
	9	-	-	259.6	159.7	318.0	218.1	376.4	276.5	493.3	393.4	610.2	510.3	308.0	208.1		
	10	-	-	236.9	125.7	295.3	184.1	353.7	242.5	470.6	359.4	587.5	476.3	342.0	230.7		
	11	-	-	-	-	271.6	150.1	330.0	208.5	446.9	325.4	563.8	442.3	376.0	254.4		
	12	-	-	-	-	-	-	-	-	424.3	290.4	541.2	407.3	411.0	277.1		
RS185	8	221.0	102.6	377.3	258.9	455.4	337.0	533.5	415.0	689.8	571.3	846.0	727.6	366.3	247.9		
	9	-	-	347.0	213.4	425.1	291.5	503.2	369.6	659.5	525.9	815.7	682.2	411.7	278.2		
	10	-	-	316.7	168.0	394.8	246.1	472.9	324.2	629.2	480.4	785.5	636.7	457.2	308.5		
	11	-	-	-	-	363.1	200.6	441.2	278.7	597.5	435.0	753.8	591.3	502.6	340.1		
	12	-	-	-	-	-	-	-	-	567.2	388.2	723.5	544.5	549.4	370.4		
RS210	8	-	-	644.0	402.2	764.9	523.1	885.8	644.1	1,127.9	885.8	1,369.9	1,127.9	565.0	323.2		
	9	-	-	603.6	331.6	724.5	452.5	845.4	573.4	1,087.7	815.1	1,328.7	1,056.8	635.6	363.6		
	10	-	-	563.2	260.9	684.1	381.8	805.0	502.7	1,046.5	744.5	1,288.5	986.3	706.3	404.0		
	11	-	-	-	-	643.8	311.3	764.7	432.2	1,006.4	673.9	1,248.4	915.8	776.8	444.3		
	12	-	-	-	-	603.3	240.6	724.2	361.5	965.9	603.3	1,208.2	845.1	847.5	484.8		

* 科仁加公司保留以上数据得最终解释权，如有变更，恕不另行通知，请咨询0531-88588198。

2015年5月23日